

Above

The fixture emits soft comfortable downlight. The conical shape and the matt, white-painted inside help assure even distribution of the light. The opening in the top of the fixture provides decorative illumination of the arch above, and ensures that the fixture retains the full expression of its visual shape both when illuminated and when switched off.

Project name:

Project type:

Notes:



Finish

White, matt or Black, matt, wet painted.

Mounting

Suspension type: Cable 2x0,75mm² (Ø175/250) Cable 2x1,00mm² (Ø400) Cable 2x0,75mm² with wire (Ø550). Canopy: Yes. Cable length: 3m (Ø175/250/400), 4m (Ø550).

Class

Ingress protection IP20. Electric shock protection II.

Materials

Shade: Spun aluminium.

Sizes and weights

Width x Height x Length (mm) | 550 x 660 x 550 Max 3.7 kg | 175 x 210 x 175 Max 0.6 kg | 250 x 300 x 250 Max 1.0 kg | 400 x 480 x 400 Max 2.4 kg

Light source & energy class

A+ - E | 1x100W E27

**louis
poulsen**

Design to Shape Light

Product description

The design is based on a half sphere with a reinforcing crossguard mounted on an U-post.
A half shield, a clear diffuser or an opal diffuser covers the lamp.
The maritime design underlines the robustness of the fixture.
Different colour variants.
Part of a family.

EU:

In-ground struts: Yes. Terminal block positioning: In fixture head.

TC-DEL: Terminal block: 1x4x2.5mm². Cable entries: 2x rear entries. 1x top entry, 1x side entry in each side and 3x bottom entries. Looping: Approved, max. 4x1,5mm².

LED: Terminal strip: 1x5x6mm². Cable access: 6 rear and 3 push-out blanks on each side, Ø19mm. Looping: Approved, max. 4x2.5mm².

Ballast positioning: In fixture head. Max. installation cable: 1 pcs. 4x2,5mm² or 2 pcs. 4x1,5mm².

US:

Integral electronic constant current, class II driver for 120-277V operation.

Back plate dimension: 9.4" diameter. Mounts over outlet box. Requires 4 x 0.2" bolts and anchors or similar hardware suitable for wall material (not provided). Caulking required between wall and back plate for wet locations (not provided).

Light description

The fixture emits asymmetrical light directed downwards or symmetrical light outwards.

The opal diffuser creates a soft light distribution.

The half shield and opal version creates a comfortable non-glaring light distribution.

The version with clear diffuser gives a significant light.

LED technology with more options of standard CCTs.

Electronic driver

Design

Mads Odgård

Mounting

Housing, half shield and crossguard: Die cast aluminium. EU: Painted in aluminium colour or graphite grey, powder coated finish. 2mm thick. US: Painted in aluminium colour or silver grey, powder coated finish. 0.08" thick.

Reflector: Highly reflective white finish symmetrical reflector for general lighting or asymmetric reflector for downlighting. 1.0mm (0.04") thick.

Enclosure: Injection moulded UV stabilized clear or opal polycarbonate. 2.5mm (0.1") thick.

Diffuser: sandblasted glass. 2mm (0.08") thick.

Heat sink: Aluminium.

U-post: Extruded aluminium. EU: Painted in aluminium colour or graphite grey, powder coated finish. US: Painted in aluminium colour, powder coated finish.

Weight

Min: 0.645 kg Max: 3.653 kg

Dimensions

Ø 175, Ø 250, Ø 400, Ø 550

Finish

Black, White

Product variants

Dimension	Light source	Colour	Cable type	Variant number
Ø 175	1x60W E27	Black	BLK TEX	5741099362
Ø 175	1x60W E27	White	BLK TEX	5741099359
Ø 250	1x60W E27	Black	BLK TEX	5741099388
Ø 250	1x60W E27	White	BLK TEX	5741099375
Ø 400	1x100W E27	Black	BLK TEX	5741099401
Ø 400	1x100W E27	White	BLK TEX	5741099391
Ø 550	1x100W E27	Black	BLK TEX	5741099427
Ø 550	1x100W E27	White	BLK TEX	5741099414

Spare parts & accessories

Product	Variant number
CANOPY BLACK 2-PART, TOPHAT ®	5749329021
ABOVE PEND 250 ANTI-GLARE SHADE MAT	5741910483
ABOVE PEND 400/550 ANTI-GLARE SHADE MAT	5741910496